



Amana
HIGH PERFORMANCE HAS A NAME™

PTAC & PTH UNITS

PACKAGED TERMINAL AIR CONDITIONERS AND HEAT PUMPS

STANDARD FEATURES

Energy Efficiencies: With EERS up to 12.1 and COP's up to 3.4, this units high efficiencies may qualify you for many of the rebates offered by electrical power companies.

Quiet Operation: This unit has been redesigned to be the quietest PTAC Amana has ever built. The unit's state-of-the-art design and construction provide a quiet environment, allowing you to enjoy peaceful, sleep-filled nights. *Two fan motors (indoor/outdoor) Indoor tangential fan for quiet operation STC of 28*

Increased Dehumidification Capacity: Maintain lower humidity levels in rooms while cooling them without the need for expensive add-ons. As a result you will feel more comfortable at higher temperatures, thus reducing cooling costs.

7-Button Touch Pad: Provides complete control for in-room comfort while maintaining energy efficiency.

5-Year Limited Warranty: Enjoy one of the most comprehensive warranties in the industry. See the back-side of this sheet for additional information.

100% Run Tested: All units are run tested in Fayetteville, TN, including leak checks during manufacturing and again prior to shipment.

7 5/8" Unit Front Depth: Enhance valuable room space with the slim unit front, one of the shallowest in the industry today.

Removable Condenser Shroud: Easy access to enable regular cleaning of the coils which is essential for maintaining unit efficiency and protecting the compressor life.

Easy Pull-Out Filters: The filters are washable and easy to maintain.

Filter Dryer for Sealed System Refrigerant: Standard in all units to protect the compressor and lengthen the life of the unit by removing moisture and preventing acid formation.

Assembled in the USA for 30 years: Assembled in Fayetteville, TN, using Goodman resources including engineering, production and testing.


Deml
HEATING & AIR CONDITIONING
Family Owned and Operated Since 1969
1500 E. Main Street
Owatonna MN 55060



507-451-6388

PRODUCT SPECIFICATIONS - PTC and PTH

PTC MODEL Cooling / Electric Heat		PTC 073E**AXXXX	PTC 093E**AXXX	PTC 123E**AXXX	PTC 153E**AXXX
Voltage		230 / 208	230 / 208	230 / 208	230 / 208
Capacity (BTU/h)		7,600 / 7,500	8,700 / 8,500	11,500 / 11,200	14,000 / 13,600
Amps		3.5 / 3.5	4.1 / 4.1	5.6 / 5.6	7.0 / 7.0
Watts		650 / 630	775 / 725	1095 / 1075	1415 / 1375
EER		11.7 / 11.9	11.2 / 11.7	10.5 / 10.4	9.9 / 9.9
UNIT WITHOUT ELECTRIC HEATER					
Min. Circuit Amps		4.2	5.0	6.8	8.5
CFM (Cool/Wet Coil)	High	290	290	290	290
	Low	264	264	264	264
CFM (Dry Coil)	High	310	310	310	310
	Low	282	282	282	282
Ventilated Air, CFM (Fan Only)*		65*	65*	65*	65*
Dehumidifications (Pints/Hr)		1.7	2.2	3.6	4.4
Net Weight (lbs)		99	103	106	117
Ship Weight (lbs)		114	118	123	134

PTH MODEL Cooling / Heat Pump / Electric Heat		PTC 073E**AXXXX	PTC 093E**AXXX	PTC 123E**AXXX	PTC 153E**AXXX
Voltage		230 / 208	230 / 208	230 / 208	230 / 208
Capacity (BTU/h)		7,600 / 7,500	9,000 / 8,900	11,500 / 11,100	14,000 / 13,900
Amps		3.5 / 3.5	4.1 / 4.1	5.6 / 5.6	7.0 / 7.0
Watts		650 / 620	770 / 765	1095 / 1065	1460 / 1465
EER		11.7 / 12.1	11.7 / 11.6	10.5 / 10.4	9.6 / 9.5
UNIT WITHOUT ELECTRIC HEATER					
Min. Circuit Amps		4.2	5.0	6.8	8.5
CFM (Cool/Wet Coil)	High	290	290	290	340
	Low	264	264	264	314
CFM (Dry Coil)	High	310	310	310	360
	Low	282	282	282	332
Ventilated Air, CFM (Fan Only)*		65*	65*	65*	65*
Dehumidifications (Pints/Hr)		1.7	2.2	3.6	4.4
Net Weight (lbs)		108	112	115	126
Ship Weight (lbs)		123	127	132	143

* Approx. 95 CFM with optional power vent kit. Actual vent CFM performance will vary due to application and installation conditions.

5-YEAR LIMITED WARRANTY

1st Year: Parts & Labor. 2nd through 5th year: Parts & labor on certain sealed system components. 2nd through 5th year: On certain functional parts only. For complete warranty details, visit www.amana-ptac.com

